

Type			T1, Heat pump	T1, Heat pump	T1, Heat pump
Control type			remote	remote	remote
Rated cooling capacity		BTU	12,000	18,000	24,000
Rated heating capacity		BTU	13,000	19,000	26,000
Energy Class	SEER	W/W	6.2	6.3	6.3
	Cooling		A++	A++	A++
	SCOP	W/W	4.0	4.0	4.0
	Heating		A+	A+	A+
Indoor noise level	Low	dB(A)	19	27	30
	Med.	dB(A)	26	35	38
	High	dB(A)	34	40	41
	Turbo	dB(A)	40	43	44
Outdoor noise level		dB(A)	52	55	58
Electrical Data					
Power supply			220-240V 50Hz	220-240V 50Hz	220-240V 50Hz
Refrigerating System					
Refrigerant			R410A	R410A	R410A
Fan System					
Indoor air circulation		m ³ /h	550	815	1100
Indoor fan type			Cross Flow	Cross Flow	Cross Flow
Outdoor fan type			Propeller fan	Propeller fan	Propeller fan
Connections					
Connecting Pipe	Gas	Inches	3/8"	1/2"	5/8"
	Liquid	Inches	1/4"	1/4"	1/4"
Others					
Net dimensions (W x H x D)	Indoor	mm	777×250×205	910×290×205	1010×315×220
	Outdoor	mm	700×550×255	780×605×290	902×650×306
Net weight	Indoor	kg	8.5	10	13
	Outdoor	kg	25	37	50
Packing dimensions (W x H x D)	Indoor	mm	850×315×275	975×366×276	1095×385×300
	Outdoor	mm	800×355×585	880×660×395	1015×720×425
Gross weight	Indoor	kg	10.5	13	16
	Outdoor	kg	29	42	59
Loading quantity	40HQ	pcs	275	203	140